

Vital-Cath™

Closed Suction System

Better Design, Better Patient Comfort



For Neo / Ped



Vitaltec Corporation

No. 12, Lane 4-30, Chyuan-Zhou Rd.,
Hou-Li Dist., 42142 Taichung City, TAIWAN

Website: www.vitaltec.com.tw

TEL: +886-4-2558-0886

Vital-Cath™

Closed Suction System

For Adult

Specifications

Product Code	Outer Diameter	Catheter Length	Remark	Packaging	ISO Colour
60100A / 60100AM 62100A / 62100AM	10FR / 3.33 mm	540mm	Endotracheal	20ea/box	●
61100A / 61100AM 63100A / 63100AM		305mm	Tracheostomy		
60120 / 60120M 62120 / 62120M	12FR / 4.0 mm	540mm	Endotracheal	20ea/box	○
61120 / 61120M 63120 / 63120M		305mm	Tracheostomy		
60140 / 60140M 62140 / 62140M	14FR / 4.67 mm	540mm	Endotracheal	20ea/box	●
61140 / 61140M 63140 / 63140M		305mm	Tracheostomy		
60160 / 60160M 62160 / 62160M	16FR / 5.3 mm	540mm	Endotracheal	20ea/box	●
61160 / 61160M 63160 / 63160M		305mm	Tracheostomy		

■ M = with MDI port (OPTIONAL)
■ All adult size Vital-Cath™ package includes disconnect wedge and corrugated adapter.



For Adult

It has unique patented suction control switch, providing a comfortable ergonomic grip and allowing easy and quick single hand operation.

- Ergonomic suction control switch with security lock and an easy single hand operation design
- Catheter with smooth edge of tip and side holes



For Neonatal & Pediatric

It is designed for high-frequency ventilation and easy endotracheal/ tracheostomy tube adaptor interchange. Different from adult ranges, this series features lightweight and the Y-adaptor with minimal dead space connector incorporated with MDI port.

- Minimal dead space adaptor incorporated with MDI port
- Not made with DEHP
- Colour depth indicator

Vital-Cath™ Neo / Ped Plus

Closed Suction System

with “Y” Endotracheal tube adaptors

Specifications

Product Code	Outer Diameter	Catheter Length	Packaging	Y-Adaptor	ISO Colour
6000500 / 6000500M	5FR / 1.67 mm	305mm	20ea/box	2.0 / 2.5 mm	●
6000600 / 6000600M	6FR / 2.0 mm	305mm	20ea/box	2.5 / 3.0 / 3.5 mm	●
6000700 / 6000700M	7FR / 2.33 mm	305mm	20ea/box	3.0 / 3.5 / 4.0 mm	●
6000800 / 6000800M	8FR / 2.67 mm	305mm	20ea/box	3.5 / 4.0 / 4.5 mm	●
6001000 / 6001000M	10FR / 3.33 mm	405mm	20ea/box	4.5 / 5.0 / 5.5 mm	●

■ M = with MDI port (OPTIONAL)



Safety



Quality



Innovation